



**Ausführung 3C – oD (offene Drahtausführungsschlitze) Darst. C, nach DIN 41 305
mit geschlitztem Zwischenflansch**

*Model 3C – oD (open wire lead-out slots) version C, to DIN 41 305
with slotted intermediate flange*



Type	Ka	Art. Nr.	Wz.	a	b	c	d	d1	f	l	l1	l2	l5	s2	z1	z2	x3
EI 150a/41,7	1	23262.4	211	40,7	41,7	107,0	122,0	-	40,1	73,0	79,0	89,0	-	2,0	-	-	-
EI 150a/41,7	2	23263.5	211	40,7	41,7	107,0	122,0	-	40,1	73,0	79,0	89,0	-	2,0	34,8	34,8	-
EI 150b/51,7	1	23264.6	211	40,7	51,7	107,0	132,0	-	40,1	73,0	79,0	89,0	-	2,0	-	-	-
EI 150b/51,7	2	23265.7	211	40,7	51,7	107,0	132,0	-	40,1	73,0	79,0	89,0	-	2,0	34,8	34,8	-
EI 150c/61,7	1	23266.8	211	40,7	61,7	107,0	142,0	-	40,1	73,0	79,0	89,0	-	2,0	-	-	-
EI 150c/61,7	2	23267.9	211	40,7	61,7	107,0	142,0	-	40,1	73,0	79,0	89,0	-	2,0	34,8	34,8	-